

ZP` ;" ;PK° ' P] 300KG

d]

d] 5



CARACTERÍSTICAS	TR300	TR300F
INCLINACIÓN MOTORIZADA-MOTORIZED TILTING	●	●
GIRO 360°-360° STROKE-END	●	●
PROTECCIÓN ELECTRÓNICA ALTA FRECUENCIA-ELECTRONIC HIGH FREQUENCY PROTECTION	●	●
INVERSOR DE MARCHA-INVERSION SENSE OF ROTATION	●	●
MASA ROTANTE INCORPORADA-INCORPORATED ROTATING MASS	●	●
SELECTOR DE CONTROL DE ROTACIÓN (PULSO/AUTOMANTENIMIENTO)-ROTATION CONTROL SELECTOR (I/A)	●	●
MANDO CONTROL (RVMAI) ARRANQUE PARADA, AJUSTE VELOCIDAD, INCLINACIÓN Y EMERGENCIA	●	●
ARRANQUE PROGRESIVO DE PLATO-PLATE START DELAY	—	●
SOLAPE ELECTRÓNICO Y RETORNO A CERO-ELECTRONIC OVERLAP AND RETURN TO ZERO POSITION	—	●
CONTROL PARA 2 GENERADORES-WELDING POWER SOURCE ENABLING CONTROL	—	●
CONTROL DESVANECIMIENTO-FADING CONTROL	—	●

ACCESORIOS	TR300	TR300F
BPR40 BRAZO AJUSTABLE NEUMÁTICO PARA TORCHA	○ ¹	○
BPR40 BRAZO MECÁNICO PARA TORCHA REGULABLE - ADJUSTABLE TORCH HOLDER MECHANICAL ARM	○	○
TARJETA FUNCIONES COMPLETA- FULL FUNCTION BOARD	○	●
JUNTA ROTANTE- ROTATING JOINT **	○	○
PEDAL ARRANQUE PARADA - START-STOP PEDAL (1PEDAL) **	○	○

● Serie / Series ○ Opcional / Options — No disponible / Not available

** Válida solo si se pide con la máquina- valid only if ordered with the machine

1 Disponible previo compra tarjeta funciones completa - Available subject to previous purchase of Full Function board